



PROPYPLAST S.A.S.
 BP 11
 Rue de l' Industrie
 43130 Retournac
 France
 Tel : 04 71 65 20 72
 Fax : 04 71 65 75 31
 E-mail : propyplast@propyplast.fr
 www.propyplast.fr

USfta94.doc

TECHNICAL DATA SHEET

SPC MSB 150

« SPC MSB » is a polypropylen cast-film for In-Mould Labelling application.
 This film is suitable for PE injection-moulding and can be printed by all conventional processes. The high UV stabilisation allows outdoor utilizations.

Color : white

Application : this film is dedicated to every outdoor application based on a PE structure

Updated : March, 23_ 2009

PROPERTIES	TEST METHOD	UNIT	VALUE
WEIGHT	DOCQ104	gr/m ²	141.1 +/- 5%
DENSITY	DOCQ104	gr/cm ³	0.941
YIELD	DOCQ104	in ² /lb	4,981
GLOSS (60°)	DOCQ106	%	5
SLIP (dyn. coef. of friction)	DOCQ109	/	0.33
YOUNG MODULUS	DOCQ109	MPa	690
TENSILE STRENGTH	DOCQ109	MPa	MD 15.0 TD 14.0
ELONGATION	DOCQ109	%	MD 440 TD 30
CORONA TREATMENT (after extrusion, on printable side) only one side of SPC MSB film is printable	DOCF002	dyn/cm	> 44

This information is given in good faith for general guidance only and no warranty is implied